

Specification:

This non-provisional application does reference and claim benefit of an earlier provisional application having a 07/10/2001 filing date and application number 60/303,884.

Title of Invention:

Wind (Water) Turbine with Centrifugal Weight Control

Background of Invention:

This invention is applicable to USPTO Classification 290 Sub-Classifications 43-44-53-55.

Today's wind and water turbines employ a variety of solutions to insure a constant operating speed (RPM). These include passive stall, active stall, pitch control and guide vanes. Each of these techniques effectively avoids capture of additional energy in an increasing flow so that rpm's can remain constant. A constant operating speed is necessary for 60 and 50 cycle (**cycles per second**) electrical environments on and off shore. Wind (and water) speeds above a given range are taken out of play in that these solutions do not transform additional energy into electricity at higher flow speeds. In a wind assumption the blades are pitched such that less surface is presented to an increasing wind. In a water assumption guide vanes are further closed to deflect the increased flow of water.

Brief Summary of Invention:

The WT/CWC permits the capture and transformation of energy in an increasing flow (wind or water) while maintaining a desired operating speed. It does not, like other systems, avoid or deflect increases in flow to maintain operating speed. As the speed of a flow increases the weights of the CWC are extended. Such extension increases the rolling torque on the low speed shaft while maintaining desired rpm's. This CWC action permits capture and transformation of additional offered kinetic energy. **Said extension of weights result in increases in**

in rtial forc s that are responsible for maintaining speed (rpm's) while increasing available rolling torque on the low speed shaft. This additional rolling torque is employed to drive additional generators under clutch control.

Brief Description of the Several Views of the Drawings:

- Figure #1 - side view complete wind system
- Figure #2 - top & side view of centrifugal weight
- Figure #3 - front view of complete wind system
- Figure #4 - top down view of complete water system

In both drawings the CWC has a vertical position relative to rotors & wheels.

This is principally for illustrative purpose and incidental to claims made.

Reference numerals:

5. wind direction

6. Nacelle

7. Weight

8. Jackscrew

9. Guide

10. Low Speed Shaft

11. Motor for Jackscrew Control

12. Blades

13. Tower

14. Guide hole

15. Top view fig #2

16. Jackscrew – female

17. Side View fig #2

18. Direction of Water Flow

19. CWC (centrifugal weight control assembly) fig # 4

20. Gearbox

21. Generators

Detailed Description of the Invention:

The WT/CWC design, which manipulates centrifugal weight to control rotor speed (and consequently generator speed) will deliver more energy as wind (or water) speeds increase while maintaining a desired operating speed (rpm's). At higher wind or water speed increments, additional generators will be brought into play as the foot-pounds of rolling torque on the low speed shaft increase.

In a water assumption, operating speed is typically controlled by guide vanes that open and close to regulate the amount of water that flows past the wheel (typical operation of a Francis Wheel). In a water turbine with CWC the low speed shaft would extend onto shore where CWC would then be applied. Only the rotor, low speed shaft and necessary infrastructure would be in the water (see figure # 4). All other components (CWC / gearbox / generators / control /etc.) would be on shore.

Description of WT/CWC: (*Figures 1,2, & 3*)

1. At the far end of an extended low speed shaft (**fig.1#10**) are weights that extend up and down on their guides as wind speeds increase or decrease. These weights are on guides and move up and down with a "jack screw" type gear (**fig.1#7-8-9**). The guides anchor on a hub that is at the downwind end of the low speed shaft. The guides are simply steel rods on which the weights (**fig.2#14-15-16-17**) extend or retract as a function of wind speed. This "controlled action" will deliver a constant rotor speed and increasing foot-pounds of rolling torque as wind speeds increase above minimum (1st cut-in) speed.
2. In an increasing wind, extending weights farther away from the hub delivers an increasing centrifugal force (**inertial force**) that in turn holds rotor speed constant while delivering more rolling torque. As available rolling torque increases, additional generators (**fig.4 #21**) are brought into play and greater amounts of electrical energy are realized.

3. The “controlled action” is the synchronous movement of the centrifugal weights closer to or farther from their hub depending on wind speed. The weights, guides and jackscrews have minimal aerodynamic impact. In below figures and in bench test three weights, guides and jackscrews radiate from the hub. Having twice as many may prove to be a more stable and responsive design in full scale.
4. The jackscrews are under motor control that is, in turn, under microprocessor control. Maintaining desired rpm's, weight position and clutch control for 2nd & 3rd cut-in intervals will necessitate re-calibration / modification of existing algorithms that control multiple operations.